




|                          |                    |
|--------------------------|--------------------|
| Pressure rating weldolet | 500 bar (7500 psi) |
| Material                 | 316L               |
| Thread                   | NPT 3/4-14         |

Only to be used with correct pressure rating on the SRV/SRD sensor.



Units: mm  
[inch]

## WOL-34NL Weldolet for pipes 2.5" and larger


This drawing remains property of rheonics. It may be neither copied nor informed to third persons or competitors without our approval. ( 2 paragraph 1 fig.7 copyright act of 9th Sept. 1965)

Protected by US and International patents granted and pending

rheonics • Switzerland • USA • [www.rheonics.com](http://www.rheonics.com) • [info@rheonics.com](mailto:info@rheonics.com) +41 52 511 32 00 +1 713 364 5427


rheonics 

inline process  
density and viscosity  
monitoring




Outer diameter must be larger than  $\Phi 70\text{mm}$ .  
For  $\Phi 60.3\text{mm}$ , use WOL-34NS

SRV-NPT



SRD-NPT



Units: mm [inch]

# Installation drawing WOL-34NL

This drawing remains property of rheonics. It may be neither copied nor informed to third persons or competitors without our approval. ( 2 paragraph 1 fig.7 copyright act of 9th Sept. 1965)

rheonics



inline process  
density and viscosity  
monitoring

Protected by US and International patents granted and pending

rheonics • Switzerland • USA • www.rheonics.com • info@rheonics.com +41 52 511 32 00 +1 713 364 5427